



Premium 95% Shielded, Stranded RG-59 Coax Cable

Comprehensive's CVC-59ST is the same X-tra-flexible RG-59 that we use to make our famous premium cable assemblies! This lightweight cable is the best RG-59 you've ever used . . . bar none! Constructed with a 22 AWG stranded bare copper center conductor for maximum flexibility. CVC-59ST amazingly provides performance superior to most solid conductor RG-59 cable. Our cellular foam polyethylene dielectric is wrapped with a very tightly woven, 95% bare copper braid shield that achieves an ultra-low nominal capacitance per foot of 17.5. Finished with our industry preferred, X-traflex, non-glare black matte finish. Once you've used CVC-59ST, you'll wonder why you ever used anything else! Use our premium BP-3C7559 true 75 ohm three piece BNC connector, CT-1 crimp tool and CTD-002 die to terminate.



Specifications

- Coax Quantity: 1
- Center Conductor: 22 AWG Stranded Bare Copper
- Dielectric: .140" Foam Polyethylene
- Shield: 95% Bare Copper Braid
- Impedance: 75 Ohms
- Capacitance per Ft: 17.3 pF/ft
- NOM Velocity of Propagation: 78%
- Bulk Lengths: 500/1000
- Jacket: PVC
- Jacket Color: Black
- Overall Diameter: .240"
- UL Rating: CM
- Temperature Rating: 75 deg C
- RoHS Compliant: Yes
- Warranty: Lifetime



CVC-59STXF-500
CVC-59STXF-1000

500 ft. Roll
1000 ft. Roll