



Pro AV/IT Series VGA HD 15 Pin Plug to Plug Cables

Since 1974, Comprehensive Pro AV/IT Series Cables have been trusted by Pro AV and I.T. systems integrators because of their legendary reliability, performance and value. That's why they have been the "go to" cable worldwide for boardrooms, classrooms, data centers, schools, government installations, stadiums, broadcast studios, stages and other mission critical applications. Pro AV/IT Series Cables are also perfect for anyone looking for premium quality connectivity at great price.



Don't be fooled by cheap imitations, there is no equal to Comprehensive Pro AV/IT series HD15 VGA cables. These cables are true high resolution construction with three individually 95% shielded 26 gauge coaxes for maximum signal transfer and high resolution video and graphics. The entire cable is then 100% shielded with a foil shield to eliminate EM and RF interference, even over long distances. A durable low profile mold provides maximum strain relief and durability. Comprehensive goes the extra mile with machined pins which ensures the strength of each pin, to make sure they do not bend or break as imitation cables often do. Comprehensive HR Pro series cables provide thousands of connections and a lifetime of worry free use. UL and RoHS compliant. Lifetime Warranty.

Features

- HD15 Male to HD15 Male
- 26 Gauge low loss construction supports high-resolution imaging up to QXGA 2048x1536
- 3 individually 95% tinned copper braid shielded coaxes
- 100% aluminum foil shield wrap provides extra coverage
- Low Profile Design for easy connecting in tight spaces
- Machined pins that stand up to 1,000's of connections
- Molded strain relief for unsurpassed durability
- X-traflex jacket for easy installation
- UL and RoHS Compliant
- Lifetime Warranty



Specifications

Performance Grade: Better
 Connector Type 1: HD15 Male
 Connector Type 2: HD15 Male
 Resolution: SVGA through QXGA (2048x1536)
 Gauge: 26AWG
 Center Conductor: Tinned Copper
 Connector Finish: Nickel
 Shielding: Triple Shielded, Inner Bare Copper Wrap, Outer 100% Aluminum Mylar Wrap, 95% Braid
 Attenuation @100MHz at 100ft: 5.460dB

Attenuation @400MHz at 100ft: 11.109dB
 Attenuation @1000MHz at 100ft: 19.423dB
 UL Rated: Yes
 Ferrite Cores: No
 RoHS Compliant: Yes
 Cable outer diameter: 0.35" (9.0 mm)
 Jacket Type: Xtra-Flex PVC
 Temperature Rating: 80 deg C
 Voltage: 30V
 Warranty: Lifetime

VGA15P-P-3HR	3ft.	VGA15P-P-35HR	35ft.
VGA15P-P-6HR	6ft.	VGA15P-P-50HR	50ft.
VGA15P-P-12HR	12ft.	VGA15P-P-100HR	100ft.
VGA15P-P-25HR	25ft.		