



HDMI and USB-A 3.0 Pass-Through Single Gang Aluminum Wall Plate with Pigtail

Comprehensive's WPPT-HD-U3A-AC Pass-through single gang HDMI and USB 3.0 Wall Plate is perfect for your transition to in-wall cabling. The pass-through ports include thin, flexible pigtail cables that accommodate the tight bend radius required for installations within a standard junction box. The included USB 3.0 Type A port supports data transfer speed up to 5Gbps and compatible with USB 2.0 and 1.1 devices. Constructed of brushed anodized aluminum, this Pass-Through wall plate offers a clean and professional appearance to reduce cable clutter.

Pass-Through Receptacles and Pigtails

Each HDMI and USB receptacle includes an attached thin, flexible pigtail cable to accommodate the tight bend radius required for installations within a standard junction box.

High Quality and Durability

Constructed of high quality brushed anodized aluminum, the wall plate is durable and long lasting for commercial usage including offices, meeting spaces, classrooms, hotels, houses of worship and other spaces requiring HDMI room connectivity.

USB 3.0 Port features 5Gbps Data Speed

The USB 3.0 Type A port provides speed and data transfer rate at up to 5 Gbps and backward compatible to USB 2.0 & 1.1 versions.

Cuts Down on Cable Clutter

This pass-through wall plate offers a clean and professional appearance and helps reduce cable clutter in professional spaces.

Quick and Easy Installation

Comprehensive's aluminum wall plate fits all standard single gang cut-outs and installs in minutes.

Lifetime Warranty

This pass-through wall plate comes with Comprehensive's Lifetime Warranty for a lifetime of worry-free use.

Features

- Single Gang Brushed Anodized Aluminum Plate
- One (1) HDMI Female Port (with HDMI female pigtail)
- One (1) USB 3.0 Type A Female Port (with USB 3.0 Type A pigtail)
- Quick and easy to install
- Durable commercial construction
- Lifetime Warranty



WALL PLATES

WPPT-HD-U3A-AC



HDMI and USB-A 3.0 Pass-Through Single Gang Aluminum Wall Plate with Pigtail

Specifications

Performance & Resolution

Performance Grade: Commercial Grade

Signal Technology Version: HDMI 1.4 & 2.0, USB 1.1, 2.0 & 3.0

Connections

Connector Front: HDMI female Type A x 1, USB 3.0 female Type A x 1

Connector Rear: HDMI female Type A x 1, USB 3.0 female Type A x 1

Environmental

Humidity: 5%-95%

Operating Temperature: 0°C to 70°C

Storage Temperature: -20°C to 70°C

Physical Characteristics

Bend Radius: 1.3"

Cable Outer Diameter (OD): HDMI : 7.5 mm

USB: 4.0 mm

Color: Black

Wallplate Dimension Width: 2.75"

Height: 4.48"

Depth: 0.125"

Cable length: 6"

Directional: No

Gauge (AWG): 28 AWG

Jacket Type: PVC

Packaging: Sealed bubble Bag

Shielding: Braided 65%

Regulatory Compliant

ATC Certification: No

CE: No

CL3 Rated: No

Prop 65 Compliant: No

Rohs Compliant: Yes

UL Rated: No

Warranty

Lifetime

Weight (Shipping)

0.65 lbs

What's In The Packaging

Single Gang Aluminum wallplate with pigtail cables x 1

UPC

808447082401

WALL PLATES

WPPT-HD-U3A-AC